



**CCL TRADITIONAL ENGLISH GUN PRODUCTS LTD.**

**CCL GUNSTOCK GRAIN SEALER**

Revision no.3  
Supersedes 24/11/2009  
Dated 4/6/2015  
Printed on 18/02/2016  
Page no. 1/12

## SAFETY DATA SHEET

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

**1.1. Product identifier:** CCL 5S/ 5L  
Product name CCL Gunstock Grain Sealer/ CCL Schaft-Maserungversiegler ( Porenfüller)  
CCL Obturateur pour grain de bois / Compuesto CCL para de sellado de poros de madera

**1.2. Relevant identified uses of the substance or mixture :** Wood Finishing  
**Uses advised against:** Anything other than the identified use

**1.3. Details of the supplier of the safety data sheet** Name CCL Traditional English Gun Products Ltd  
Full address The Gun Room, Park Cottage,  
District & Country Bentley Lane, Upper Bentley  
Redditch, B97 5TD  
Worcestershire,  
England, United Kingdom.  
Telephone Tel./Fax: +44 (0)1527550080  
e-mail address of the competent person ccl.gunprodltd@btconnect.com  
responsible for the SafetyData Sheet

**1.4. Emergency telephone**  
For urgent inquiries refer to:  
+44 (0)1527 550080 0900-1700 Monday to Friday, NHS 111 SERVICE (24 Hour General Public) National Emergency Telephone Number  
National Poisons Information Service (24hours) 0844 8920111. Emergency Telephone Nr. in Germany +49(0)30 /19 240

### SECTION 2. Hazards identification.

#### 2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

##### 2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments.

Hazard classification and indication:  
Flam. Liq. 2 H225  
Eye Dam. 1 H318

##### 2.1.2. 67/548/EEC and 1999/45/EC Directives and following amendments and adjustments.

Danger Symbols:  
F-Xn  
R phrases:  
11-20/21/22-36

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

#### 2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.



CCL TRADITIONAL ENGLISH GUN PRODUCTS LTD.

Revision no.3

Dated 4/6/2015

Printed on 18/02/2016

Page n. 2/12

CCL GUNSTOCK GRAIN SEALER

Hazard pictograms:



Signal words: Danger

Hazard statements:

H225 Highly flammable liquid and vapour.  
H318 Causes serious eye damage.

Precautionary statements:

P210 Keep away from heat / sparks / open flames / hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P280 Wear protective gloves / protective clothing / eye protection / face protection.  
P303+P361+P353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.  
P310 Immediately call a POISON CENTER or doctor / physician.  
P370+P378 In case of fire: Use . . . for extinction.

Contains: BUTANOL

### 2.3. Other hazards.

Information not available.

## SECTION 3. Composition/information on ingredients.

### 3.1. Substances.

Information not relevant.

### 3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification 67/548/EEC.	Classification 1272/2008 (CLP).
<b>BUTANOL</b>			
CAS. 71-36-3	5 - 6	R10, R67, Xn R22, Xi R37/38, Xi R41	Flam. Liq. 3 H226, Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3H335, STOT SE 3 H336
EC. 200-751-6			
INDEX. 603-004-00-6			
<b>METHANOL</b>			
CAS. 67-56-1	2,5 - 3	F R11, T R23/24/25, T R39/23/24/25	Flam. Liq. 2 H225, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT SE 1H370
EC. 200-659-6			
INDEX. 603-001-00-X			



**CCL TRADITIONAL ENGLISH GUN PRODUCTS LTD.**

Revision no.3

Dated 4/6/2015

Printed on 18/02/2016

**CCL GUNSTOCK GRAIN SEALER**

Page n. 3/12

#### ZINC STEARATE

CAS. 557-05-1 1.5 - 2 Substance with a community workplace exposure limit.

EC. -

INDEX. -

#### Phenol, isopropylated, phosphate(3:1)

CAS. 68937-41-7 1 - 1.5 Repr. Cat. 3 R62, Repr. Cat. R63, Xn Repr. 2 H361, STOT RE 2H373, Aquatic Chronic R48/22, N R51/53 2H411

EC. -

INDEX. 273-066-3

Note: Upper limit is not included into the range.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

T+ = Very Toxic(T+), T = Toxic(T), Xn = Harmful(Xn), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizing(O), E = Explosive(E), F+ = Extremely Flammable(F+), F = Highly Flammable(F), N = Dangerous for the Environment(N)

## SECTION 4. First aid measures.

### 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

### 4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

### 4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

## SECTION 5. Firefighting measures.

### 5.1. Extinguishing media.

#### SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

#### UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

### 5.2. Special hazards arising from the substance or mixture.

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

### 5.3. Advice for firefighters.

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).



**CCL TRADITIONAL ENGLISH GUN PRODUCTS LTD.**

Revision no.3

Dated 4/6/2015

Printed on 18/02/2016

Page n. 4/12

**CCL GUNSTOCK GRAIN SEALER**

## SECTION 6. Accidental release measures.

### 6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage.

### 7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s).

Information not available.

## SECTION 8. Exposure controls/personal protection.

### 8.1. Control parameters.

Regulatory References:

United Kingdom EH40/2005 Workplace exposure limits. Containing the list of workplace exposure limits for use with the Control of Substances Hazardous to Health Regulations (as amended).

Éire Code of Practice Chemical Agent Regulations 2011.

OEL EU Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.

TLV-ACGIH ACGIH 2012



CCL GUNSTOCK GRAIN SEALER

**BUTANOL  
Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
OEL	IRL		20			SKIN
TLV-ACGIH		61	20			
WEL	UK			154	50	SKIN

**METHANOL  
Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
OEL	EU	260	200			SKIN
OEL	IRL	260	200			SKIN
TLV-ACGIH		262	200	328	250	
WEL	UK	266	200	333	250	SKIN

**Zinc Stearate  
Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
OEL	EU	10	4	20		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

**8.2. Exposure controls.**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Ensure emergency washing facilities are available in an emergency to shower face and eyes

**HAND PROTECTION**

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SKIN PROTECTION**

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344).

Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

**EYE PROTECTION**

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

**CCL GUNSTOCK GRAIN SEALER****RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

**ENVIRONMENTAL EXPOSURE CONTROLS.**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

**SECTION 9. Physical and chemical properties.****9.1. Information on basic physical and chemical properties.**

Appearance	liquid
Colour	light cream
Odour	characteristic of solvent
Odour threshold.	Not available.
pH.	Not available.
Melting point /freezing point.	Not available.
Initial boiling point.	> 35 °C.
Boiling range.	Not available.
Flash point.	< 23 °C.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	0.835 Kg/l
Solubility	Not available.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

**9.2. Other information.**

Information not available.



**CCL TRADITIONAL ENGLISH GUN PRODUCTS LTD.**

Revision no.3

Dated 4/6/2015

Printed on 18/02/2016

Page n. 7/12

**CCL GUNSTOCK GRAIN SEALER**

## **SECTION 10. Stability and reactivity.**

### **10.1. Reactivity.**

There are no particular risks of reaction with other substances in normal conditions of use.

BUTANOL: attacks various types of plastic.

### **10.2. Chemical stability.**

The product is stable in normal conditions of use and storage.

### **10.3. Possibility of hazardous reactions.**

The vapours may also form explosive mixtures with the air.

BUTANOL: reacts violently developing heat with: aluminium, strong oxidising agents, strong reducing agents, hydrochloric acid.  
Forms explosive mixtures with the air.

### **10.4. Conditions to avoid.**

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

BUTANOL: avoid exposure to sources of heat and naked flames.

### **10.5. Incompatible materials.**

Information not available.

### **10.6. Hazardous decomposition products.**

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

## **SECTION 11. Toxicological information.**

### **11.1. Information on toxicological effects.**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product may cause serious ocular lesions, cornea opacity, iris lesions, irreversible eye coloration.

METHANOL: The minimal lethal dose following ingestion is considered to be in the range of 300-1000 mg/kg. Ingestion of as little as 4-10 ml methanol in adults may cause permanent blindness (IPCS).

BUTANOL  
LD50 (Oral). 790 mg/kg Rat  
LD50 (Dermal). 3400 mg/kg Rabbit  
LC50 (Inhalation). 8000 ppm/4h Rat



**CCL TRADITIONAL ENGLISH GUN PRODUCTS LTD.**

Revision no. 3

Dated 4/6/2015

Printed on 18/02/2016

Page n. 8/12

**CCL GUNSTOCK GRAIN SEALER**

Zinc Stearate

LD50 (Oral). > 5000 mg/kg ORALRat

LD50 (Dermal). > 2000 mg/kg DERMRabbit

ETHYL CELLULOSE

LD50 (Oral). > 5000 mg/kg rat

LD50 (Dermal). > 5000 mg/kg rabbit

## SECTION 12. Ecological information.

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil, sewers and waterways. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

### 12.1. Toxicity.

Information not available.

### 12.2. Persistence and degradability.

Information not available.

### 12.3. Bioaccumulative potential.

Information not available.

### 12.4. Mobility in soil.

Information not available.

### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### 12.6. Other adverse effects.

Information not available.

## SECTION 13. Disposal considerations.

### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Avoid littering. Do not contaminate soil, sewers and waterways.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## SECTION 14. Transport information.

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations.

These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.





CCL TRADITIONAL ENGLISH GUN PRODUCTS LTD.

Revision no. 3

Dated 4/6/2015

Printed on 18/02/2016

Page n. 9/12

CCL GUNSTOCK GRAIN SEALER

**Road and rail transport:**



ADR/RID Class: 3 UN: 1263  
Packing Group: II  
Label: 3  
Nr. Kemler: 33  
Limited Quantity: 5 L  
Tunnel restriction code: (D/E)  
Proper Shipping Name: PAINT or PAINT RELATED MATERIAL

**Carriage by sea (shipping):**



IMO Class: 3 UN: 1263  
Packing Group: II  
Label: 3  
EMS: F-E , S-E  
Marine Pollutant: NO  
Proper Shipping Name: PAINT or PAINT RELATED MATERIAL

**Transport by air:**



IATA: 3 UN: 1263  
Packing Group: II  
Label: 3  
Cargo:  
Packaging instructions: 364 Maximum quantity: 60 L  
Pass.:  
Packaging instructions: 353 Maximum quantity: 5 L  
Special Instructions: A3, A72, A192  
Proper Shipping Name: PAINT or PAINT RELATED MATERIAL

**SECTION 15. Regulatory information.**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.**

Seveso category. 7b

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.  
Point. 3 - 40

Substances in Candidate List (Art. 59 REACH).

None.



CCL TRADITIONAL ENGLISH GUN PRODUCTS LTD.

Revision nr. 1

Dated 4/6/2015

Printed on 18/02/2016

Page n. 10/12

CCL GUNSTOCK GRAIN SEALER

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

#### 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

### SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
STOT SE 1	Specific target organ toxicity - single exposure, category 1
Acute Tox. 4	Acute toxicity, category 4
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Dam. 1	Serious eye damage, category 1
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H361	Suspected of damaging fertility or the unborn child.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.



**CCL TRADITIONAL ENGLISH GUN PRODUCTS LTD.**

Revision no. 3

Dated 4/6/2015

Printed on 18/02/2016

Page n. 11/12

**CCL GUNSTOCK GRAIN SEALER**

H331	Toxic if inhaled.
H370	Causes damage to organs.
H302	Harmful if swallowed.
H373	May cause damage to organs through prolonged or repeated exposure.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

R10	FLAMMABLE.
R11	HIGHLY FLAMMABLE.
R20/21/22	HARMFUL BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.
R22	HARMFUL IF SWALLOWED.
R23/24/25	TOXIC BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.
R36	IRRITATING TO EYES.
R37/38	IRRITATING TO RESPIRATORY SYSTEM AND SKIN.
R39/23/24/25	TOXIC: DANGER OF VERY SERIOUS IRREVERSIBLE EFFECTS THROUGH INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.
R41	RISK OF SERIOUS DAMAGE TO EYES.
R48/22	HARMFUL: DANGER OF SERIOUS DAMAGE TO HEALTH BY PROLONGED EXPOSURE IF SWALLOWED.
R51/53	TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
Repr. Cat. 3	Reproductive toxicity, fertility, category 3.
R62	POSSIBLE RISK OF IMPAIRED FERTILITY.
Repr. Cat. 3	Reproductive toxicity, development, category 3.
R63	POSSIBLE RISK OF HARM TO THE UNBORN CHILD.
R67	VAPOURS MAY CAUSE DROWSINESS AND DIZZINESS.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration



**CCL TRADITIONAL ENGLISH GUN PRODUCTS LTD.**

Revision no. 3

Dated 4/6/2015

Printed on 18/02/2016

Page n. 12/12

**CCL GUNSTOCK GRAIN SEALER**

- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

1. Directive 1999/45/EC and following amendments
2. Directive 67/548/EEC and following amendments and adjustments
3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
6. Regulation (EC) 453/2010 of the European Parliament
7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
8. Regulation (EC) 618/2012 (III Atp. CLP) of the European Parliament
9. The Merck Index. - 10th Edition Handling Chemical Safety
10. Niosh - Registry of Toxic Effects of Chemical Substances
11. INRS - Fiche Toxicologique (toxicological sheet)
12. Patty - Industrial Hygiene and Toxicology
13. N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
14. ECHA website

#### Notes for users.

The information contained in this data sheet is provided in accordance with the requirements of the Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) The product should not be used for purposes other than those shown in Section 1.2. As the specific conditions of use are outside the suppliers control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet is based on the present knowledge and the current EC and UK Legislation. It provides guidance on safe handling, use, processing, storage, transportation, disposal, release and environmental aspects of the product and should not be taken as a product specification or warranty. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text or in the instructions for use accompanying the product. Users should read and understand the product instructions for use and those using quantities for commercial work should be given adequate training on how to use chemical products.

#### Disclaimer:

The company supplying this data sheet shall not be held liable for any damage resulting from handling or from contact with the above product.

Date supplied 06/11/2019